

3M™ Overhead Projector Model 1608

Budget

Low Priced, Feature-Packed

The 3M™ Model 1608 may be low in cost, but it's still packed with the features you need to deliver clear, bright images in your classrooms and presentations. The 2,000 lumens of brightness enhance your visuals even when room lights are on. The extra sturdy construction delivers years of reliable use.



KEY FEATURES

- > Open singlet projection head for easy cleaning
- > 2,000 lumens enhance your visuals even with the room lights on
- > No assembly required
- > 11.25" x 11.25" staging area gives you room to maximize your message
- > Lamp Changer enables instant bulb replacement
- > Fold-down post allows easy storage
- > High/Low switch provides options for lamp brightness. Low setting generally lengthens lamp life
- > Color Tuning dial gives you the ability to adjust the clarity and the whiteness of the screen
- > 2 Year Warranty

ORDER NUMBER: HK-4000-0009-5

UPC Code: 0-51125-60655-4

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, dust cover, and projection screens.

TECHNICAL SPECIFICATIONS

OPTICAL PERFORMANCE

- > Head: Open singlet (*one element*)
- > Illumination: 2,000 ANSI lumens typical
- > Stage aperture: 285.75 mm x 285.75 mm (*11.25" x 11.25"*)
- > Stage temperature: 46°C (*115°F*)
- > Focal Length: 280 mm (*11"*)

LAMP DESCRIPTION

- > Lamp changer: Yes
- > Lamp Type: EHJ (*24 volts, 250 watts*)(2 Lamps included)
- > Lamp Life: 50 hours average

PHYSICAL CHARACTERISTICS

- > Width: 343 mm (*13.5"*)
- > Depth: 343 mm (*13.5"*)
- > Height(body): 267 mm (*10.5"*)
- > Weight: 30 lbs. (*13.6 kg*)

ELECTRICAL FEATURES

- > Power-cord length: 3 m. (*10'*)
- > Voltage rating: 120VAC, 60Hz
- > Agency approval: UL/cUL

MECHANICAL

- > Thermal protection circuit: cuts power to the lamp if the projector exceeds safe operating temperature.
- > Fold-down post



www.3M.com/meetings

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

3M Visual Systems

Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000
1-800-328-1371
www.3m.com/meetings

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Visual Systems

3M Canada Company
P.O. Box 5757
London, Ontario, Canada
N6A 4T1
1-800-364-3577

Litho in U.S.A. © 3M 2005

78-6970-8567-4 Rev. B

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of two years from the time of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M Innovation